



# **STORA SUPER 200 - H300** with F900 slotted ductile iron gratings, 10mm slot







#### **OPTIONS**

- •Universal endcap with integrated outlet Ø160
- •Sump unit
- •Stepped fall
- •Also available in heights 130, 180 and 240
- •Available in 0.5m length with outlet 390x130

## EN1433:2005



F900

### DESCRIPTION

Polyester concrete drainage channel with cast iron protective edge profile, width 200, height 300 and 2 gratings F900 ductile iron, 10mm slot. Solid construction, good chemical resistance, integrated ductile iron profile, with security joint.

### ADVANTAGE PRODUCT

- •Grating: 2 gratings ductile iron, 10mm slot
- •Waterway area of the 2 gratings: 8,60 dm<sup>2</sup>
- •Hydraulic capacity of the 2 gratings: 56,50 L/sec
- •Opening between bars <20mm. To guarantee the accessibility of public places for disabled persons, the slots of the gratings with the disabled-symbol are never larger than 20mm.
- •Gratings with unique anti-skid surface
- •Predrilled vertical outlet Ø200mm
- •Grating fixing system: 1 M10 stainless steel bolt per grating + 2 integrated, in the profile, ridges
- •The channels are assembled against each other by means of a tongue and groove jointing system (male/female); to ensure the channels watertightness it is recommended to use a suitable elastic polyurethane sealant.
- •Cascade installation possible in combination with heights 180 and 240.

#### MATERIAL

- •Channel: polyester concrete
- •Protective edge profile: ductile iron GJS 500-7 following EN1563 •Grating: ductile iron GJS 500-7 following EN1563

#### COATING

Grating: Non-toxic and non-polluting black water paint

#### CERTIFICATION

Certified EN1433:2005

#### PLACE OF INSTALLATION

Group 6, Class F900  $\rightarrow$  see EN1433:2005 Areas subjected to especially high wheel loads (e.g. aircraft pavements). Only longitudinal use, never transverse direction.

REFERENCE	ARTICLE N°	KG	UNITS PER PALLET
Stora-Super 200 H300 slotted gratings F900 ductile iron, 10mm slot.	SU20301325	77,5	12

Sizes in mm - Weights, sizes and sketch are indicative - Uncontrolled distribution.

STORA-DRAIN is a brandname of n.v. IMCOMA s.a. (responsible editor) • Zwaarveld 32 • B-9220 Hamme phone: +32 (0)52 499 899 • fax: +32 (0)52 470 776 • e-mail: info@imcoma.com